

Instrument Syphon

Model: MDS1

Applications

- Dissipates elevated live steam temperature
- Rugged design for direct mounting
- Reduces process temperature to protect attached instrument
- Process industry: Chemical/petro chemical, power stations, food and beverage, offshore oil rigs, pulp and paper, environmental technology, machine building and general plant construction

Special features

- All stainless steel 316L
- Pressure ranges up to 1000 bar

Description

- **Body material** Stainless steel 316L
Hastelloy, Monel, Tantalum(option)
- **Process connection** Stainless steel 316L
¼ NPT, ½ NPT, BSP (option)



MDS1 Instrument Syphon

| ORDERING CODE | Example: | MDS1 | 4 | M | U | OS | Note |
|--|----------|------|---|---|---|----|------|
| Process Connection Sizes | | | | | | | |
| 2 - ¼ NPT | | | | | | | |
| 4 - ½ NPT | | | 4 | | | | |
| 6 - ¾ G | | | | | | | |
| 8 - 1½ G | | | | | | | |
| 10 - Customer | | | | | | | |
| Body material | | | | | | | |
| B - Brass | | | | | | | |
| S - 316L Stainless steel | | | | | | | |
| M - Monel® 400 | | | | M | | | |
| H - Hastelloy | | | | | | | |
| C - Customer | | | | | | | |
| Shape | | | | | | | |
| S - Spiral | | | | | | | |
| U - U shape | | | | | U | | |
| T - Straight | | | | | | | |
| C - Customer | | | | | | | |
| Options | | | | | | | |
| OS - Overload stop | | | | | | OS | |
| NS - According to NACE MR 0175 & NACE MR 0103 standard | | | | | | | |

Other sealing



Address: 7191 Yonge street, Toronto, Canada

Tel: +16472221281(5 line)

Web: www.madecotech.com

Email: Info@madecotech.com