

All Stainless steel Bimetal Thermometers Model: T11

Applications

- General process instrumentation in the chemical and petrochemical industries, pulp & paper, refineries, pharmaceutical/biotech, food and beverage, energy and water/wastewater industries.
- Temperature measurement in harsh and aggressive environments
- Silicone damened coil for reductions and provides improved response times

Special features

- Scale ranges from -70 ... +600 °C
- Individual stem length from 63 ... 1,000 mm
- Adjustable stem length
- All stainless steel construction

Description

- | | |
|---------------------------|--|
| ■ Accuracy class | 1.6% |
| ■ Dial size | 3"(80mm), 4"(100 mm), 5"(125mm), 6"(160mm) |
| ■ Case & bayonet bezel | 304 stainless steel (std.) epoxy painted 304 st. steel or 316 stainless steel (option) |
| ■ Measuring element | Bimetal coil |
| ■ Process connection | movable, fixed or plain |
| ■ Process connection size | 1/2 NPT |
| ■ Stem length | 63...500mm |
| ■ Stem diameter | 6mm (std.) 6.4 mm, 8mm, 9.6 mm & 12.7 mm (option) |
| ■ Window | Glass (std.) plexiglass, Laminated safety glass (option) |
| ■ Max. operating press | 360 psi |
| ■ Max. process temp. | 115% of the full scale |
| ■ Dial | Aluminium, white, black lettering |
| ■ Range | 0...10 to 0...30,000 psi; |
| ■ Protection | IP65 |





TI 1 Bimetal Thermometers

ORDERING CODE	Example: TI1	4	T	0	4	F	AT	120	WA	Note
Dial Size										
3 - 80 mm(3")										
4 - 100mm(4")		4								
5 - 125mm(5")										
6 - 160mm(6")										
Connection Type										
T - Bottom			T							
B - Back										
Stem Diameter										
0 - 6.0 mm (standard)				0						
2 - 6.4 mm (1/4")										
4 - 8.0 mm (5/16")										
6 - 9.6 mm (3/8")										
8 - 12.7 mm (1/2")										
C - Customer										
Stem length										
2 - 63 mm										
4 - 100 mm					4					
6 - 150 mm										
8 - 200 mm										
10 - 250 mm										
15 - 300 mm										
20 - 500 mm										
XXX - Please specify the length (mm)										
process connection										
F - Fixed						F				
M - Movable										
P - Plain										
C - Customer										
Accuracy										
AT - 1.6%							AT			
Range (°C)										
XXX - Please specify the range								120		
Options										
L F - Liquid fill										
SC - Single scale										
DS - Dual scales										
YW - 316L Stainless steel case										
EP - Epoxy painted case & bezel										
SG - Safety glass										
BT - BSP thread										
CC - Calibration certificate										
NH - Stainless steel tag wired to case										
AT - ATEX										
WA - One year warranty									WA	
WR - Two year warranty										
NC - NACE MR 0175 & MR 0103 standard										
Other										





Address: 7191 Yonge street, Toronto, Canada

Tel: +16472221281(5 line)

Web: www.madecotech.com

Email: Info@madecotech.com