MDINC4 Gigabit Ethernet Network Card



Features

- Intel® Ethernet Controller®X550-AT2
- Two adaptive 100M/1G/10Gbps RJ45 interfaces
- Support five network speed standards: 10G/5G/2.5G/1G/100M
- Transmission via Cat5/Cat6 or higher specification cables
- Support full height/half height bracket

Product specification

System	
Port type	2x RJ45
Ethernet Controller	Intel® X550-AT2
Interface	PCI express x4, PCIe (Gen3) compatible with PCIe x8/x16
Speed	100M/1G/2.5G/5G/10Gbps
Meet a criterion	IEEE-1588
Indicator light	Speed LED: 100M: Off, 1G: Orange, 10G: Green Link LED: Active connection (Green) Transmit/reveive activity(Blinking Green)
Power consumption	13W max (2x10Gb/s active)
Cable requirements	For 10GBASE-T: CAT6a (100 meters) or CAT6 (55 meters) For 5Gb/s NBASE-T: CAT6 (100 meters) For 2.5Gb/s NBASE-T: CAT5e (100 meters)
Jumbo frames	Support jumbo frames, up to 15.5kb
Power input	PCIe slot
Operating system	Win7/Win10/Linux
Environment	
Operation temperature	0℃ ~ 60℃
Storage temperature	-40℃ ~ 85℃
Humidity	Operation hum: 95%@40℃, non-coagulation Storage hum: 95%@60℃, non-coagulation
Mechanism	
Size	149*68.9mm (without bracket)
Certification	
Safety certification	CE, FCC

Industrial Computer

network card	MDINC-G02L-I210 2-port PCIE network port	2 Ethernet ports - PCIE Ethernet port
	MDINC-G04L-I210 4-port PCIE network port	4-ports PCIE port
	MDINC-G4PL-I210 4-port POE Ethernet port	4-ports POE network card
	MDINC -X550 2-port 10 Gigabit Ethernet card	2-ports 10 Gigabit Ethernet card
Touch screen integrated machine	MDINC-PD156	15.6-inch CPU: J6412/Memory: 8G/Storage: 128G/2LAN
	MDINC-PD156	15.6-inch/CPU: I5-10310U/Memory: 16G/Storage: 1TB SSD/2LAN
	MDINC-PD190	19 inch/CPU: J6412/Memory: 8G/Storage: 128G/2LAN
	MDINC- D190	19 inch/CPU: I5-10310U/Memory: 16G/Storage: 1TB SSD/2LAN



Address: 7191 Yonge street, Toronto, Canada

Tel: +16472221281(5 line)

Web: www.madecotech.com

Email: Info@madecotech.com